

Heating Electrification Strategies to Decarbonize BU's Major Buildings: January 2022 update


1. Decarbonization framework for BU
2. Technical Constraints & Design Implications
3. Financial Analysis & Policy Questions
4. Summary of Deep & Quick Decarbonization Strategy



Sabrina Dilig (ENG '23), Cathy Cheng (ENG '23), Gayatri Sundar Rajan (ENG '22), Professor Michael Gevelber
Mechanical Engineering, Boston University

Decarbonization Framework

- 40% of BU's total GHG emissions come from heating loads. 274 buildings (11.8 M GSF)
- Strategy: Electrify 14 largest buildings to reduce up to 46% of heating GHG emissions
- **How can we electrify the greatest % of BU's fossil heating systems, in the shortest time, meeting building heating requirements, & capital/operating budget constraints?** → solutions applicable to existing, commercial buildings



Heating Electrification Technology Tradeoffs

- Air- vs Ground- source Heat Pumps: ASHPs are less efficient than GSHPs and require more capacity on coldest days b/c of de-rating, but require 2X less capX
- High Temp vs Low Temp Heat Pumps: High-temp HPs produce heating fluid compatible with existing perimeter heat exchangers, but are less efficient and require more capX than low-temp HPs
- Natural Gas boiler (baseline) & conventional Electric Boiler: lower capX and efficiency compared to heat pumps
- Note: COP quantifies efficiency, therefore a higher COP = lower OpX
- Analysis based on in-depth detailed studies of several BU buildings

	Conventional Fossil	Conventional Electric	Low-Temp (130°F) Heat Pumps		High-Temp (180°F) Heat Pumps	
	Natural Gas Boiler	Electric Boiler/ Resistance	Low-Temp Air-Source Heat Pumps	Low-Temp Ground-Source Heat Pump	High Temp Air-Source Heat Pump	High Temp Ground-Source Heat Pump
	NG Boiler	Conventional Electric	ASHP/LT	GSHP/LT	ASHP/HT	GSHP/HT
Coefficient of Performance COP	0.85	1.0	3.0	5.0	<u>2.0</u>	<u>2.5</u>
System Equipment Cost per Ton (\$/Ton) [2]	\$200	\$200	\$2,700	\$9,500 [1]	\$3,600	\$8,600 [1]

[1] GSHP equipment costs include installed cost of bore hole

[2] Equipment costs for >200 Ton systems

Constraints: Technical Requirements for Retrofitting Existing Building


Key Considerations:

- 1) Relation of **required heating power** to equipment sizing
- 2) **Capacity factor** of equipment (cost-effectiveness, utilization)
- 3) **Heating fluid temps** for existing building heat exchangers
- 4) Increased **electrical demand** relative to building capacity

Design Question:

Which configurations / combinations of heating equipment can best meet these consideration?

Critical Heating System Characteristics




Model building: 380K ft² office / classroom with ~350 ton heating load

Required Heating Capacity: Impact on CapX, OpX, & GHG emissions

- Typically, equipment sized to meet heating demand on coldest day
- However, only ~20% of the heating season has temp <30F


Hybrid Solution:

- Size expensive heat pumps for 45% of peak heating demand → reduces CapX
- Use conventional boilers for coldest days
- Increases Heat Pump Capacity Factor to 64%
- Achieves 92% GHG reduction




Financial Analysis of Alternative Electrification Strategies

- Electrification is a net cost increase compared to BAU
- BERDO ACP cost (\$234/Mton of CO2e) increases “cost” of operating existing NG Boilers
- Capital limitations → GSHP Hybrids ~1.6x the CapX of ASHP Hybrids w/ similar NPV. Does it limit roll out?



Estimated Compliance Time Frame & Costs:

Boston BERDO 2.0 University Requirements & Current BU Campus Emissions



Electrification Summary for Fast & Deep Decarbonization

- **Hybrid strategy**: achieves high-capacity factor for heat pumps, reduces CapX to enable faster rollout, meets heating demand on coldest days, achieves 90% carbon reduction.
 - ASHPs vs GSHPs: ASHPs are ~40% cheaper than GSHPs in CapX, but are ~20-40% less efficient
 - Hybrid Incremental cost: \$100/MT CO₂ [relative to \$234 ACP & BAU] 92% carbon reduction
- **Estimated Impact under BERDO (whole BU campus)**: a) BU doesn't need to start changes till 2030. b) First round: cheapest to buy green electrons (depends on price conditions in 2030-2040 time frame), c) ACP impact for heating electrification starts in 2040, \$134 savings relative to BERDO ACP [Suggestion: don't allow area to count from building parking areas]
- **Climate needs quicker action**. How to drive that? Incentives to early movers?
- **Proposed BU implementation plan**
 - 12 yr plan: Electrify 3.8M GSF (14 key buildings) to reduce 46% of BU CRC's heating fossil fuel use
 - CapX: \$3.5M/yr (\$32.2M investment) Annual OpX: \$10.3M/yr
 - Post-Electrification OpX will be 40% less than existing NG system with BERDO ACP
- **Key Issues for Spring 2022**
 - Capacity and COP vs. OA, heat recovery for summer reheat, buildings on steam loops, ASHP and heat exchanger configuration, and refining cost estimates

Acknowledgements

We'd like to sincerely thank the following individuals for their insight & time:

Boston University Student Researchers

Author of "BU CRC Electrification" Analysis (Jan 2018)

David Staller (ME '18)

Authors of "Energy Efficiency Opportunities on CRC" Analysis (May 2017)

Gabriella Henkels, Charles Bradley Miller, Ryan Peters, Carly Baracco, Anthony Graziano, Cole Ashman Paul Chiampa Jr., Jessica Gimbel, Cristian Morales

Estimating Costs & Financing Large CapX Projects

Domenic Armano	President, Guardian Energy Management
Phillip Eash-Gates	Senior Associate, Synapse Energy Economics
Michael Gibbs	Former Assistant Executive Officer, CARB; Former Deputy Secretary of Climate Action, CalEPA; Former Senior Vice-President, ICF International;
Megan Howard	Director, MassCEC
Judith Judson	VP of Distributed Energy Systems, Ameresco
Robert Kaufmann	Earth & Environment Professor, Boston University Founding Partner, First Fuel Software;
Jeremy Koo	Associate, Cadmus Group
Nalin Kulatilaka	Business Professor, Boston University Founding Partner, First Fuel
Paul Lyons	President, Zapotec Energy Inc

Understanding Boston University's Planning, HVAC Implementation, & Budget

Dennis Carlberg	Director of Sustainability, Boston University
Robb Dixon	Former Chair, Boston University Faculty Council
Shaun Finn	Assistant VP of Budget, Planning & Business Affairs, Boston University
Dipak Intwala	Manager of Boston University Energy Efficiency Program
Joseph Kajunski	Assistant Director of Boston University Engineering and Building Automation
Paul Rinaldi	Assistant VP for Planning, Boston University

Understanding Building HVAC Design & Heat Pumps

Bradley Campbell	President, Conservation Law Foundation
Nicholas Conklin	Director of Global Product Strategy, Carrier HVAC Program
Cris Copley	Principal of HVAC & Mechanical Design, BR+A
Robert Fisher	VP of Facilities, Roxbury Community College
Anthony Hardman	Senior BPA, The Green Engineer Inc.
Jacob Knowles	Director of Sustainable Design, BR+A
Paul Kondrat	Principal, CannonDesign
James McQueen	Project Manager, Boston Arts Academy
Carolyn Meadows	Director of Strategic Initiatives, Boston Arts Academy
Joshua Michaud	Associate Principal of HVAC, BR+A
Chris Schaffer	Founder & President, The Green Engineer Inc.
Neetu Siddharth	Principal, The Green Engineer Inc.
Timothy Simpson	AERMEC Product Specialist, Emerson Swan
Mike Walters	Principal & Expert in Distributed Heating Systems, Salas O'Brien

Geothermal: Heating & District Heating

T.J. Bernier	Gap Mountain Drilling
Keeley Bombard	BU Earth & Environment (CAS '22)
Owen Brady	Manager of Future of Heat Program, National Grid
Jarred Mullen	Skillings and Sons
Tracey Ogden	Principal, TAO Consulting
Erik Pekkala	Growth Portfolio Lead of New Energy Products, National Grid
Nathan Phillips	BU Earth & Environment Professor, Boston University ⁹

Additional Slides

Constraint: Heating Fluid Temperatures

Key Question: How well will low-temperature (130F) heat pumps perform in buildings with existing high-temperature (170-190F) hot water heat exchangers (perimeter heat, VAV, AHU)?


Motivation: Determining whether we can use low-temperature heat pumps (lower capX, higher COP) in hybrid heat pump system and provide required thermal comfort throughout the heating season.

Results:

- Our analysis shows 130F hot water provides required heat when outside air temps are ≥ 31 F [1]
- When temps are < 31 F, use NG/Electric Boilers for supplemental heating with higher temperature working fluids (only 20% of heating season hours & 10% of energy used)

Conclusion:

- Low-temp heat pump hybrid strategy will meet heating needs [2]
- Enables 90% GHG emissions reduction



[1] Verified by Sterling HS application manuals

[2] Strategy applicable to both ASHPs and GSHPs


Cost of Reducing Carbon Emissions: NPV & CapX

- Boston BERDO's Alternative Compliance Payment (ACP): \$234/MTCO_{2e} Corresponds to 2.2X NG price (\$1.07/therm → \$2.31/therm)


Insight:

- Hybrid systems provide *cost savings* vs NG system with BERDO ACP (y-axis), minimize CapX needs for heating electrification, w/ 92% GHG reduction
 - Hybrid Electric Boiler + ASHP/LT systems can achieve 100% reduction: but would require increase in electric capacity

Cost of Reducing Carbon Emissions




CapX to Reduce Carbon Emissions




Heat pump impact on Electrical Capacity & Peak Demand

- For Hybrid System: ASHP/LT & existing NG boiler
- **New heating season electrical peak but less than existing cooling season peak**
- Building electrical capacity upgrade not required for 90% decarbonization retrofit



100% Decarbonization: ASHP/LT & Electric Boilers

- 90% → 100% decarbonization strategy: Replace existing NG boilers with electric boilers
- Change in electrical demand: Expect increase of ~0.9 MW on coldest days
- Outcome: Although peak electrical demand exceeds summer peak, **2.0 MW need < 13.6 MW supply** → may not require building electrical upgrades to operate



Hybrid System: operation with higher capacity factors

- Using Heat Pumps & Boilers: Increases Capacity Factor (CF) of Heat Pumps but decreases total GHG emission reduction
 - Capacity Factor (CF): % of time one uses an expensive CapX system → Higher CF enables more efficient utilization of expensive heat pump
 - 31% → 64% Capacity Factor: increases cost-effectiveness of high CapX heat pumps
 - 89% of heating Energy Use: Indicates % of GHG reduction if NG boiler used to supplement heat pump

