

Styling Reference

Styling Backgrounds

FORM:

```
<body style="background: color image repeat-setting attachment position">
... </body>
```

color: To change background color, replace *color* with a HEX value like '#ff0000', an RGB value like 'rgb(255,0,0)' or a color name like "red".

image: To add a background image, replace *image* with *url('T.extension')* where T is the name of image (examples of extensions are .jpg, .png, .gif).

repeat-setting: For vertical repeat, replace *repeat-setting* with *repeat-y*. For horizontal repeat, insert *repeat-x*. For none, insert *no-repeat*.

attachment: For an image that scrolls with rest of page, replace *attachment* with *scroll*. For a fixed image, insert *fixed*.

position: To position background, replace *position* with X Y, where X can be *left*, *right* or *center* and Y can be *top*, *bottom* or *center*.

EXAMPLE:

```
<body style="background:#ffffff url('img_tree.png') no-repeat right top;"> </body>
```

Styling Text (can be applied to divs and p)

FORM:

```
<html_element style="color: value1; text-align: value2; text-decoration: value3;">
... </html_element>
```

color: To change font color, replace *value1* with a HEX value, RGB value or color name.

text-align: To align text, replace *value2* with *left*, *right*, *center* or *justify* to align text to the left, right, center or stretch the lines so they have equal width

text-decoration: To add line below text, replace *value3* with *underline*. To add line above text, replace *value3* with *overline*. To add strikethrough, replace *value3* with *line-through*.

E.G. <p style="color:#ffffff, text-align:center; text-decoration:underline "> </p>

Styling Fonts (can be applied to divs and p)

FORM:

```
<html_element style= "font: style weight size family"> </html_element>
```

style: To display text in italics, replace *style* with *italic*

weight: To specify font weight, replace *weight* with *bold*, *bolder*, or *lighter*

size: To specify size, replace *size* with *xx-small*, *x-small*, *small*, *medium*, *large*, *x-large*, or *xx-large*

family: To specify font, replace *family* with *Georgia*, *Arial* or *Courier New*

EXAMPLE:

```
<p style= "font:italic bold 12px/30px Georgia;"> ... </p>
```

More Useful Properties

FORM:

```
<html_element style= "margin: value; padding: value2; "> ... </html_element>
```

margin: To specify margin replace *value* with 4 numbers *top right bottom left*
E.G. <p style="margin:2 4 3 4;"> </p>

padding: To specify padding replace *value2* with 4 numbers *top right bottom left*
E.G. <p style="padding:2 4 3 4;"> </p>

For more commands, visit <http://www.w3schools.com/html/>.

For a list of colors, visit:

http://www.w3schools.com/tags/ref_colornames.asp.