

Transient Thermal Simulator Using Machine Learning

Ronni Chang^{1, 2}, Amin Khodaverdian², Ayse Coskun²



Temperature(t+1)


¹Brookline High School, Brookline, MA 02445

²Department of Electrical & Computer Engineering, Boston University, Boston, MA 02215

Introduction

Background:

➤ Increased temperature degrades performance of modern 3D chip



➤ PArallel Compact Thermal Simulator (PACT) developed by PEACLab can make accurate predictions based on numerical solvers [1]

Problems:

- Numerical solvers are time-consuming
- Neural Network solvers require ample training data

Methods

Power(t+1)

H*W

Temperature(t)

Dimensionality Reduction:

➤ Use principal component analysis (PCA) to compress high-dimensional thermal data into lower-dimensional components [2]

Fast Predictive Model:

Employ machine learning (ML) in PACT for faster and more accurate predictions of thermal distributions

Run PACT to

generate output

Run script to

generate .cir files


➤ Utilize closed-form linear regression models for speedy computations [3]

USER INPUTS

ptraces, config


file, floorplan


file, lcf file



Results

Linear regression achieves best performance in terms of least computing time (<1 min) and least mean square error (<0.1 °C)</p>





Conclusion

Summary:

➤ MLPACT is turned into a pipeline with flexible parameterization and predictive model selection, requiring only 10–15 training samples

Future Work:

- > Test on other chip architectures
- Systematically compare performance with other predictive models

References

http://bit.ly/4lZwOa7

Acknowledgements

I would like to thank Amin Khodaverdian and Professor Coskun providing me mentorship and guidance throughout this internship. I would also like to thank the rest of PEACLab for providing me with help along the way. Lastly, I would like to thank the RISE program and Boston University for giving me the opportunity to be here!